

# ENSTO

Atšakojimo gnybtas

SL37.1



Tipas	SL37.1
GTIN	6418677414404
Pavadinimas	Atšakojimo gnybtas Al 10-95 mm <sup>2</sup> ir Al 10-95 mm <sup>2</sup>
Aprašymas	Atšakojimo gnybtas SL 37.1 skirtas aliuminio laidininkams sujungti, be mechaninio itempimo. Gnybtas yra su vienu M8 varžtu.

Gamintojas

## Techninė specifikacija

### Certificates

Standartinis žymėjimas: EN 61238-1

### Dimensions

Pagrindinis laidininkas mm<sup>2</sup>: Al 10-95  
 Atšakos laidininkas mm<sup>2</sup>: Al 10-95  
 Laidininko skersmuo: 3 ... 13 mm  
 Net Weight: 0,062 kg

### Features

Varžtas: M8  
 Plastikinis gaubtas: SP15

### Mechanical

Užveržimo momentas: 22 Nm

### Others

ETIM Class: EC001062

## ETIM Techninė specifikacija

etim

Nominal cross section main conductor SE: 10 ... 95 mm<sup>2</sup>

Nominal cross section main conductor SM:	10 ... 95 mm <sup>2</sup>
Nominal cross section branch conductor SE/RE:	10 ... 95 mm <sup>2</sup>
Nominal cross section branch conductor SM/RM:	10 ... 95 mm <sup>2</sup>
Material main conductor:	Aluminium
Material branch conductor:	Aluminium
Terminal insulated:	No
Clamping channel opening main conductor:	Both sides open
Clamping channel opening branch conductor:	Both sides open
Surface protection:	Bare
Type of connection:	Screwed connection

## Packaging

---

### Pallet package

Unit:	pcs
Package size:	10800
Depth:	1200 mm
Width:	800 mm
Height:	1140 mm

### Default package

Unit:	pcs
Package size:	200
Depth:	383 mm
Width:	258 mm
Height:	173 mm
Weight:	12,742 kg
Volume:	17,094822 l