


22433 DALLA CT-DTL50-B

Ceiling-mounted spotlight fitting

5905339224330



DALLA CT-DTL50-B



Kanlux DALLA is a very carefully made holder for installation inside buildings. It has a movable ring, thanks to which you can adjust the light stream. Its shapes and universal colours allow achieving a modern, discrete effect of elegance.

GENERAL DATA:

Colour: black

Necessity of using self-shielding lamps : yes

Place of assembly: Recessed mount in the ceiling

Place of application: Indoors

Minimum distance from the illuminated object : 0,5m

The product is not suitable to be covered with a heat-insulating material: yes

Length [mm]: 82

Width [mm]: 82

Height [mm]: 26

Assembly hole [mm]: Ø70

TECHNICAL DATA:

Rated voltage [V]: 12 AC; 12 DC

Maximum power [W]: max 10

Class of protection against electric shock : III

Light source: MR16

Light source included: no

Cap: Gx5,3

Ambient temperature range to which the product can be exposed: 5÷25

Enclosure material: aluminum alloy

Connection type: Free cable ends

Wire length [m]: 0.12

Wire diameter [mm²]: 0.75

Lighting-fixture angle regulation : in one axis

Lighting-fixture angle regulation [°]: 30

IP class: 20

LOGISTIC DATA:

Unit of measurement: unit

Packaging method: 50

Number of units in the secondary packaging : 1

Number of units in the packaging: 50

Net unit weight [g]: 84

Grammage [g]: 110

Length of a unit pack [cm]: 10

22433 DALLA CT-DTL50-B

Ceiling-mounted spotlight fitting



Width of a unit pack [cm] : 4

Height of a unit pack [cm] : 10

Weight of a cardboard box [kg] : 5.5

Width of a cardboard box [cm] : 22.5

Height of a cardboard box [cm] : 22

Length of a cardboard box [cm] : 52

Volume of a cardboard box [m³] : 0.02574