FILLERS





Gel: UL 94-HB

Dielectric strength:

>20 kV/mm

Cross linking time:

fast (about 7 min. at 23°C)

Volume resistivity:

>2 . $10^{15}\,\Omega$ cm

Working temperature:

-60°C/+200°C

Overload temperature for short periods:

up to 250℃

Stabilised for:

mould - UV

Degree of protection:

IP68 (in proper casings)

Magic Gel Sprint protects against dust and seals the connections from the effects of continuous immersion in water when it is poured into casings protected from the ingress of solid bodies, thus helping to create a **IP68** system.









MAGIC GEL SPRINT

Insulating and sealing gel with very high dielectric and thermal characteristics, ideal for POWER cables, TELECOM cables and ELECTRONICS CIRCUITS.

Magic Gel Sprint is formulated for an extra fast curing directly inside the bottle. Practical, performing, eco-sustainable, it is the ideal GEL for insulating and sealing boxes of the most commonly used dimensions.

ADVANTAGES

- ► Non-toxic, safe and not classified as hazardous under CLP Directive.
- ► Suitable for installation in salt water (sea) and in chlorinated water (pools).
- For any type of indoor / outdoor and even submerged installation.
- ► For installations up to 1 kV.
- Suitable for high temperatures.
- ► Removable.
- No shelf life.





FILLERS
















Magic Gel 450 Sprint



PRODUCT / Item	Colour	Package type	Total quantity
MAGIC GEL SPRINT 450 MAGICSPRINT450	•	1 bottle + 1 catalyst	450 ml
MAGIC GEL SPRINT 900 MAGICSPRINT900	•	2 bottles + 2 catalysts	900 ml

Magic Gel 900 Sprint



MAGIC GEL SPRINT is available **in 2 version** which are sustainable in terms of packaging and in terms of volume, as they are specifically designed for filling boxes in the most commonly used formats.